



## 2" Polystyrene Insulated Sectional Doors

Amarr® 2432/2732

**Amarr 2" polystyrene insulated doors feature solid steel construction.** Two tough steel skins and an advanced 4-step insulation system make these doors strong and durable.

The Amarr 2432 has an outer skin made from heavy-duty 24-gauge steel and features a stucco embossment with shallow pencil grooves. The Amarr 2732 has an outer skin made from 27-gauge steel with the same panel design and embossment. Both doors utilize 27-gauge steel with stucco embossment for the interior skin.

The 4-step insulation system includes tongue and groove construction, CFC-free polystyrene insulation, weather-stripping, and a thermal break that provides a strong barrier from extreme heat and cold.



**CONSTRUCTION**



**Amarr 2432**  
Heavy-Duty, 2" 24-gauge steel

**Amarr 2732**  
Medium-Duty, 2" 27-gauge steel



**Rapid Install Vertical Lift:** Designed specifically for commercial warehouse and dock doors and saves approximately 20 minutes of installation time per door due to fewer jamb attachments and a pre-assembled, one-piece track.

**Track:** All Amarr doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow the Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit [www.amarr.com](http://www.amarr.com).

**Springs:** Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

**Standard Hardware:** Galvanized steel hinges and track brackets. All rollers have minimum 10-ball bearings.

**SPECIFICATIONS**

	Heavy-Duty <b>Amarr 2432</b>	Medium-Duty <b>Amarr 2732</b>
<b>STEEL THICKNESS (Exterior/Interior)</b>	24 ga / 27 ga	27 ga / 27 ga
<b>PANEL DESIGN</b>	Pencil Groove	Pencil Groove
<b>STEEL EMBOSSMENT</b>	Stucco	Stucco
<b>DOOR THICKNESS</b>	2" (5.1cm)	2" (5.1cm)
<b>CONSTRUCTION LAYERS</b>	Triple	Triple
<b>INSULATION<sup>1</sup></b>	Polystyrene	Polystyrene
<b>R-VALUE<sup>2</sup></b>	9.4	9.4
<b>U-VALUE</b>	0.106	0.106
<b>AIR INFILTRATION</b>	.18 cfm/ft2 @ 15 mph / .30 cfm/ft2 @ 25 mph	.18 cfm/ft2 @ 15 mph / .30 cfm/ft2 @ 25 mph
<b>MINIMUM WIDTH</b>	6'	6'
<b>MAXIMUM WIDTH</b>	24' 2"	24' 2"
<b>MINIMUM HEIGHT</b>	7'	7'
<b>MAXIMUM HEIGHT</b>	26' 1"	26' 1"
<b>WIND LOAD<sup>3</sup> AVAILABLE</b>	•	•
<b>PAINT FINISH WARRANTY<sup>4</sup></b>	10 Years	10 Years
<b>WORKMANSHIP/HARDWARE WARRANTY<sup>4</sup></b>	1 Year	1 Year

<sup>1</sup> Insulation has passed self-ignition, flamespread and smoke developed index fire testing. <sup>2</sup> Calculated door section R-value is in accordance with DASMA TDS-163. <sup>3</sup> It is your responsibility to make sure your garage door meets local building codes. <sup>4</sup> For complete warranty details, visit [amarr.com](http://amarr.com) or contact your local Amarr dealer.

**PANEL OPTIONS**



PENCIL GROOVE PANEL WITH STUCCO EMBOSSMENT

**WINDOW OPTIONS**



24" X 12" INSULATED GLASS  
Available with either a black or white frame.



24" X 6" DOUBLE INSULATED ACRYLIC WINDOWS WITH BLACK FRAME

**STEEL COLORS**

Amarr steel doors are pre-painted; for custom colors, exterior latex paint must be used. Visit [amarr.com](http://amarr.com) for instructions on painting. Actual paint colors may vary from samples shown.



TRUE WHITE (TW)



SANDTONE (ST)



COMMERCIAL GRAY (CY)



COMMERCIAL BROWN (CB)



**Amarr Color Zone\***  
Over 500 factory-applied colors.

Visit a Sherwin-Williams store to select the SnapDry™ paint color of your choice.



\*Price upcharge applies.



Tel: (55) 4440 0360 WhatsApp:  
(81) 8363 8981 EMAIL:  
[ventas@bering.com.mx](mailto:ventas@bering.com.mx)